

K1-107

NON-YELLOWING TRANSPARENT WATERPROOF COATING

Unique transparent waterproof coating that will adhere to all the inorganic surfaces. K1-107 is used mainly to waterproof tiled surfaces by an easy application over the surface. Eliminating the need to remove tiling and waterproof the terrace from below, but it is also use to waterproof all kind of support. It gives an impermeable, smooth, non-pigmented barrier to the surface.

Details

- Easy to apply.
- Non-Yellowing, Alkali and UV resistant.
- Long lasting transparency.
- Great elasticity and waterproofing effect.
- Shiny or matte finish.
- Protect building materials from the elements, water ingress, pollution and acid rain.

Recommend Uses

- Aluminum, Kitchen Cabinets, Varnished Woodwork, Glazed Block, Ceramic Tile, Glass, PVC Piping, Mosaic, Stone and Marble.

Applications

Surface Preparation

- All new masonry, concrete, cement or block must be cured for 30 days at recommended.
- Remove all loose paint and defective paint if possible, oil, fluid, moss or other substances on the surface. In severe cases, wash the surface with water, make sure the surface is completely dried and clean. All holes cracks must be properly patched.

Application Details

- Product must be completely agitated (mechanically or manually) before use.
- Intermix containers of same product to ensure color and seen uniformity.
- Dilution is no needed.
- Application of 2-3 coats at the recommended film thickness / practical coverage when application to new surfaces.

Technical Data

Property	Value
Tools	Nylon / Polyester Brush, Sponge Paint Roller, Sprayer
Drying Time	Touch Dry 1-2 Hours, Recoat 6-8 Hours (at 25°C)
Coverage	13 m ² Coverage per Gallon
Thickness	Wet 350 µm, Dry 120 µm
Available Sheen	Flat, Gloss
Density	1 kg/L
Viscosity	>500 m.Pas at 25°C
Available Size	1 Liter, 1 Gallon, 5 Gallon
Shelf Life	36 months unopened condition
Color	Transparent

Drying and recoat times are temperature, humidity, and film thickness dependent.

Practical coverage is for reference only, which can be differ depending on the brushing surface, flatness and film thickness.

These figures are only intended as a guide and should not be used in preparing specifications.

Storage

Product should be store in the dry and cool area, please avoid direct sunlight contact to prevent deterioration. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

After container is opened, use the product immediately and prevent long-term storage.

Cautions and Safety

- Do not use if rain or heavy dew is expected within 24 hours.

- Avoid applying the product when the temperature is below 50°F.
- KEEP OUT REACH OF CHILDREN – DO NOT TAKE INTERNALLY.
- When spraying. Do not breathe spray, wear suitable respiratory protective equipment.
- Avoid direct contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek for the medical advice.
- After contact with skin, wash with soap and water.
- Safety Data Sheet (SDS) is available on www.kingcatpaint.com.tw.

Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Yulung Paint. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Yulung Paint representatives or visit www.kingcatpaint.com.tw to obtain the most current version of the Technical Data Sheet and / or a Safety Data Sheet.