

## K2-900

# **ANTI-SLIP EMERY SAND**

Anti-Slip Emery Sand can be added to floor paint for indoor or outdoor use to increase slip resistance. Suitable applications are concrete, stone and cement screeds.

#### Details

- Natural SiC modified.
- Easy application.
- Excellent hardness.

#### **Recommend Uses**

- Indoor and outdoor concrete surfaces.
- Can be added to most KINGCAT top coat products, from floor to waterproof coatings. Gives a high quality high slip resistant finish.

### Applications

#### **Application Details**

Scattered evenly over the wet coating after application.

#### **Technical Data**

Property	Value
Tools	Scatter

Drying Time	Top coat depended
Coverage	5 GAL of top coating with 1 GAL of K2-900
Available Size	1 Gallon, 5 Gallon
Shelf Life	36 months unopened condition
Color	Gray White

Drying and recoat times are temperature, humidity, and film thickness dependent.

Practical coverage is for reference only, which can be differ depending on the brushing surface, flatness and film thickness.

#### These figures are only intended as a guide and should not be used in preparing specifications.

#### Storage

Product should be store in the dry and cool area, please avoid direct sunlight contact to prevent deterioration. Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

After container is opened, use the product immediately and prevent long-term storage.

#### **Cautions and Safety**

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F.
- KEEP OUT REACH OF CHILDREN DO NOT TAKE INTERNALLY.
- When spraying. Do not breathe spray, wear suitable respiratory protective equipment.
- Avoid direct contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek for the medical advice.
- After contact with skin, wash with soap and water.
- Safety Data Sheet (SDS) is available on www.kingcatpaint.com.tw.

#### Disclaimer

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Yulung Paint. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Yulung Paint representatives or visit www.kingcatpaint.com.tw to obtain the most current version of the Technical Data Sheet and / or a Safety Data Sheet.